

## PRODUCT DATA SHEET

### LALIZAS Fire Extinguisher PFAS Free Foam, Stored Pressure,

with wall bracket, SOLAS/MED



- Stored pressure
- Temperature ranges: +5° + 60°



CODE / **LANGUAGES** 

75939 EN, GR, CN













#### **SPECIFICATIONS**

#### **BODY - ALUMINUM**

 Seamless, deep and drawn aluminum alloy body, ensures maximum sealing and, thanks to its light weight, perfect handling. Externally painted with polyester resin.

#### **VALVE - ALUMINUM**

 Squeeze grip lever operated valve with aluminum body, ensuring perfect protection against corrosion. The shockproof pressure gauge is equipped with a non-return valve to allow pressure control and with a sintered filter to protect sensitive parts.

#### **EXTINGUISHING AGENT**

 Water with specific FLUORINE FREE additives to increase performance in class A. All parts in contact with the extinguishing agent are compatible.

#### **PROPELLANT**

• The propellant gas is nitrogen. A small percentage of helium is added to allow electronic leak detection.

#### HOSE/HORN

 The EPDM reinforced rubber hose guarantees perfect flexibility and resistance within the temperature range. Complete with nozzle.

#### **PACKAGING**

Single piece cardboard box, robust and suitable for transport.

#### STANDARD CONFIGURATION

#### **Bracket**

Button holed wall bracket



#### **Hose Rings & Protective Base**

Protective base 6/12kg ø180 green



#### Hose holder Ø180



#### **Packaging**

Box PS9 J/HJ





# PRODUCT DATA SHEET

LALIZAS Fire Extinguisher PFAS Free Foam, Stored Pressure, with wall bracket, SOLAS/MED



#### **TECHNICAL DATA**

CODE (LANGUAGES)	75939 (EN, GR, CN)	
FIRE RATINGS	27A 183B	
CHARGE	9 L 0 / -5	
MATERIAL	Aluminum	
CYLINDER	Manufacturing process	Deep Drawing
	External painting	Polyester Resin
	Corrosion resistance	480 H SECONDO ISO 9227:2017
EXTINGUISHING AGENT	WATER WITH ADDITIVES	
PROPELLANT	N2 + HE	
DISCHARGE	Discharge time	~ 75 s
PRESSURE	Operating pressure at 60 °C	16 bar
	Operating pressure at 20 °C	13 bar
	Operating pressure at 5 °C	10 bar
DIMENSIONS	Overall height	630 mm
	Bottle outer diameter	180 mm
WEIGHT	Empty / Charged	2.98 kg / 12.1 kg
PACKING SPECIFICATIONS	Standard packing	1 Pieces cardboard box
	Carton size (B x L x H)	195 x 195 x 650 mm
	Weight per carton	12.65 kg
	Pallet	48 Cartons
	Pallet size (B x L x H)	800 x 1200 x 1460 mm
	Pallet volume	1.38 m³
	Weight per pallet (net/gross)	607.2 kg / 627.2 kg



# Code Description 73648 Marine Bracket for LALIZAS Fire Extinguisher Foam, 9lt

Manufactured by: ANAFGROUP

Anaf Fire Protection S.p.A. - 27020 Torre d'Isola (PV) Italy, www.anaf.eu e-mail: info@anaf.eu



# **Global Service & Supply Network**



- ✓ Global service network through owned locations & third-party service providers
- Global supply of LSA, FFE and spare parts
- Certified quality standards by major classification societies
- ✓ Robust warranty supported directly by the manufacturer
- ✓ Streamlined after-sales support via our ticketing system

Safety is not just a product, it is an ongoing process!